






Screen Series Retail 2005 Pricelist









All prices ex. VAT and ex. Works. Effective June 2005

Stage Acccompany
 Anodeweg 4, 1627 LJ Hoorn NH, The Netherlands
 Phone: +31 (0)229 28 29 30, Fax: +31 (0)229 28 29 20
 Email: info@stage-acccompany.com, www.stageacccompany.com



That's How Music Should Sound!

Model	Description	Price (Euro)
Screen Series		
S26	<p>Screen Series</p> <ul style="list-style-type: none"> • Full-range cinema front system • Super Space Saving Design • Double SA 1203 and SA 8535S Ribbon Compact DriverTM. • Flying system • SPL 130 dB @ 2000 W peak 	<p>1200h x 1200w x 230d mm (47.2 x 47.2 x 9.1 inch)</p>  <p>2.595</p>
S26 A	Available with Active (bi-amp) or passive (single amp) filtering Please specify when ordering	2.495
S27	<p>Screen Series</p> <ul style="list-style-type: none"> • Full-range cinema front system • Super Space Saving Design • Single SA 1513 and SA 8535S Ribbon Compact DriverTM • Flying system • SPL 125 dB @ 1000 W peak 	<p>1200h x 1200w x 230d mm (47.2 x 47.2 x 9.1 inch)</p>  <p>2.195</p>
S27 A	Available with Active (bi-amp) or passive (single amp) filtering Please specify when ordering	2.095
SL15	<p>Screen Series</p> <ul style="list-style-type: none"> • Low frequency cinema front system • Super Space Saving Design • Single SA 1513 • Flying system • SPL 125 dB @ 1000 W peak • Lowest usable frequency 39 Hz. (-3dB) 	<p>1200h x 500w x 230d mm (47.2 x 19.7 x 9.1 inch)</p>  <p>1.195</p>
SL30	<p>Screen Series</p> <ul style="list-style-type: none"> • Low frequency cinema front system • Super Space Saving Design • Double SA 1513 • Flying system • SPL 131 dB @ 2000 W peak • Lowest usable frequency 39 Hz. (-3dB) 	<p>1200h x 1000w x 230d mm (47.2 x 39.4 x 9.1 inch)</p>  <p>1.595</p>
S30z	<p>Screen Series</p> <ul style="list-style-type: none"> • Cinema subwoofer front system • Double SA 1513 • SPL 131 dB @ 2000 W peak • Lowest usable frequency 25 Hz. (-3 dB) • Available without front • resonance-free and kick-proof grill in matching color (S30) 	<p>750h x 1035w x 730d mm (29.5 x 40.8 x 28.7 inch)</p>  <p>2.095</p>

Model	Description		Price (Euro)
Sb45	Screen Series <ul style="list-style-type: none"> High output cinema subwoofer front system Triple SA 1513 SPL 136 dB @ 3000 W peak Lowest usable frequency 25 Hz. (-3 dB) Available without front resonance-free and kick-proof grill in matching color (SB45) 	730h x 1190w x 670d mm (28.7 x 44.9 x 26.4 inch) 	2.995
S7	Screen Series <ul style="list-style-type: none"> Ultra compact high output cinema surround system Double 5" woofers and 1" soft-dome tweeter 2-position mounting Mounting adapter on the backside 	428h x 176w x 173d mm (16.9 x 6.9 x 6.8 inch) 	495
Bracket set	Screen Series <ul style="list-style-type: none"> Mounting bracket for S7 cabinet For wall-mount (set of 2 pcs.) 		49
Multi Color Option™	Screen Series <ul style="list-style-type: none"> All Screen Series cabinets can be supplied in every RAL color (standard black finish) 		+5%
Amplifiers			
SSA 100 Screen Series Amplifier	Amplifiers <ul style="list-style-type: none"> High specification class G power amplifier Dynamic Damping Control (DDC™) Extended Function Network (EFN™) on-board Cross-over / processing Output 2 x 530 W RMS @ 2 Ω; 2 x 710 peak @ 2 Ω Speakon-4 out / D-connector (in/out) 2 HE 	88h x 428w x 415d mm (3.5 x 19.0 x 16.3 inch) 	1.995
SSA 200 Screen Series Amplifier	Amplifiers <ul style="list-style-type: none"> High specification class G power amplifier Dynamic Damping Control (DDC™) Extended Function Network (EFN™) on-board Cross-over / processing Output 2 x 960 W RMS @ 2 Ω; 2 x 1400 peak @ 2 Ω Speakon-4 out / D-connector (in/out) 3 HE 	133h x 428w x 415d mm (5.2 x 19 x 16.3 inch) 	2.295
Screen Series			
EFN™ XP module	Screen Series <ul style="list-style-type: none"> EFN™ Cross-over module standard frequencies (24dB Bessel filter) 		99
EFN™ DP module	Screen Series <ul style="list-style-type: none"> Cross-over module Standard frequencies (24 dB / oct. Bessel filter) Power Optimizing Dedicated clip / excursion protection 		139

Please specify system set-up when ordering